

## APPENDIX 2. OPERATIONAL RATINGS

### SECTION 2.1 INSTRUMENT RATING

#### Unit 2.1.1 IREX: Instrument rating

#### 1. Reserved

#### 2. General operational knowledge

##### 2.1 Privileges and limitations conferred by an instrument rating

- 2.1.1 Describe the privileges of an instrument rating.
- 2.1.2 State the limitations of an instrument rating, including proficiency checks and recent experience requirements.
- 2.1.3 State limitations for the conduct of a flight under the IFR in a type rated aircraft.

##### 2.2 Documents

- 2.2.1 List the documents that must be carried on an IFR flight.

##### 2.3 Procedures, radiotelephony and charts

- 2.3.1 Operation and limitations of flight instruments required to conduct a flight under the IFR.
- 2.3.2 Standard radio communication phraseology used to conduct IFR operations in accordance with AIP.
- 2.3.3 Procedure to be followed in the event of loss of radio communications in different phases of flight.
- 2.3.4 Requirements for notifying ATC of changes in estimated time of arrival at waypoint in flight.
- 2.3.5 Symbology and interpretation of information published on charts used to conduct operations under the IFR.
- 2.3.6 Reporting requirements for a descent, approach and landing at an aerodrome outside controlled airspace.
- 2.3.7 Differences between 2D and 3D instrument approach operations.
- 2.3.8 Difference between the minimum altitude MDA and DA when published on an instrument approach chart and the pilot responsibilities.
- 2.3.9 How variations in temperature above and below ISA affect altimeter accuracy.
- 2.3.10 Pilot responsibilities when conducting 3D instrument approach operations in temperatures below ISA.
- 2.3.11 Validity period of flight plans submitted to ATC.
- 2.3.12 Pilot obligations for cancellation of SAR.
- 2.3.13 The circumstances in which a missed approach must be conducted.
- 2.3.14 The criteria for determining the published alternate aerodrome weather minimum specified for an aerodrome and its use in planning.
- 2.3.15 Aircraft separation standards from other IFR and VFR aircraft.
- 2.3.16 Procedure/s for operating PAL systems.
- 2.3.17 The principles of operation and limitations of runway visual approach slope lighting systems used in Australia.
- 2.3.18 Pilot responsibilities for compliance with the following procedures:
  - (a) SID;
  - (b) STAR;
  - (c) Noise abatement;

- (d) Missed approach;
  - (e) Holding pattern and entry.
- 2.3.19 Operation of aircraft transponders.
- 2.3.20 Limitations on use of radar when on the ground.

### **3. Meteorology**

#### **3.1 Weather phenomena**

- 3.1.1 Seasonal variations in the location and frequency of the following phenomena and their impact on IFR operations:
- (a) frontal weather;
  - (b) tropical cyclones;
  - (c) dust devils;
  - (d) thunderstorms;
  - (e) jetstreams;
  - (f) fog.

#### **3.2 Meteorological information**

- 3.2.1 Requirements for obtaining meteorological information to conduct a flight under the IFR.
- 3.2.2 Interpret meteorological forecasts required to conduct an IFR flight to determine the operational requirements that apply in accordance with AIP.
- 3.2.3 Given air temperature in clear air or in cloud, determine approximate height of freezing level, using a temperature lapse rate of 3°C per 1,000 ft in clear air and 1.5°C in cloud.
- 3.2.4 Given pilot observations, either in clear air or in cloud, of any 1 or more of the following phenomena — turbulence, precipitation, temperature, cloud type predict the probability and likely duration of the following:
- (a) airframe icing;
  - (b) hail;
  - (c) micro bursts and wind shear;
  - (d) turbulence (including CAT).
- 3.2.5 Interpret meteorological information required to conduct a flight under the IFR to determine the possibility of turbulence for the planned route.
- 3.2.6 Sources for obtaining updates to weather information in flight, including the Volmet service as detailed in AIP.
- 3.2.7 Obligations for reporting variations to forecast meteorological conditions.

#### **3.3 Sources of altimeter QNH required to conduct operations under the IFR**

#### **3.4 Meteorological minima**

- 3.4.1 State the minimum meteorological conditions required for take-off.

### **4. Operational planning requirements**

#### **4.1 Flight plan**

- 4.1.1 Plan an IFR flight between aerodromes in Australia in accordance with the requirements specified in AIP and considering the following:
- (a) route limitations;
  - (b) aircraft performance and forecast freezing level;
  - (c) table of cruising altitudes/levels.
- 4.1.2 Determine RNP requirements applicable to an IFR flight.

## 4.2 Alternate requirements

- 4.2.1 Describe the alternate aerodrome requirements for the following:
- (a) weather;
  - (b) navigation aids or approach procedures;
  - (c) aerodrome lighting (including personnel in attendance requirements);
  - (d) availability of weather reports;
  - (e) divert time.
- 4.2.2 Determine holding fuel requirements for:
- (a) weather; and
  - (b) traffic;
- 4.2.3 When NGT VFR operations are planned on last route segment, determine the following:
- (a) pilot night recency requirements;
  - (b) alternate requirements;
  - (c) airways clearance requirements.
- 4.2.4 Requirements when weather conditions at the planned destination deteriorate below conditions prescribed for alternate or landing minima after the flight commences.
- 4.2.5 The implications of each type of RAIM prediction on operational requirements.

## 4.3 Lowest safe altitude

- 4.3.1 Calculate LSALT for a route not specified in AIP charts.
- 4.3.2 The minimum obstacle clearance criteria for a missed approach as specified in IAL.
- 4.3.3 The minimum obstacle clearance provided by the minimum circling altitude for different performance category IFR aircraft as defined in IAL, both day and night.
- 4.3.4 The requirements for establishing the aircraft on track after take-off.
- 4.3.5 Describe the requirements to establish the aircraft above the LSALT after take-off.
- 4.3.6 The requirements that must be satisfied for descent below LSALT or minimum safety altitude by day and night under the IFR and night VFR.

## 4.4 Navigation requirements

- 4.4.1 Requirements for position fixing in accordance with the AIP.
- 4.4.2 The determination of aircraft performance category and the implications for operations under the IFR.
- 4.4.3 The requirements associated with the following waypoints and the symbology used on an instrument approach chart to define each point for the following:
- (a) initial approach fix;
  - (b) final approach fix.
- 4.4.4 The requirements to conduct visual circling by day or night.
- 4.4.5 The use of PEC when applied to a DA to determine AOM.
- 4.4.6 The normal gradient applied in each segment when designing an instrument approach procedure.
- 4.4.7 Tracking tolerance requirements for the following:
- (a) avoidance of CTA;
  - (b) utilising ground based navigation aids;
  - (c) when nav aids are not available;
  - (d) notification requirements;
  - (e) order of precision of navigation aids/systems.
- 4.4.8 Speed limitations and restrictions in accordance with the AIP for the following:
- (a) operations below 10 000 ft AMSL;

- (b) during holding procedures;
- (c) during approach procedures;
- (d) issued by ATS and when speed restrictions are cancelled.

## **5. Ground and space-based navigation systems and infrastructure**

### **5.1 Ground-based systems**

- 5.1.1 For ground-based radio navigation aids:
  - (a) understand the principles of operation, indications and limitations of the ground-based navigation aids; and
  - (b) extract from AIP:
    - (i) the rated coverage of the radio navigation aids considering aircraft location, altitude and time of day; and
    - (ii) pilot navigation tolerances.
- 5.1.2 For lateral azimuth guidance provided by NDB, describe the following:
  - (a) the errors caused by coastal refraction;
  - (b) the effect thunderstorms may cause;
  - (c) the indications of loss of signal integrity;
  - (d) the potential for errors when turning;
  - (e) the indications of station passage.
- 5.1.3 Given heading and relative NDB azimuth bearings, for the following:
  - (a) calculate track to and from the NDB;
  - (b) fix position given relative bearings of 2 stations;
  - (c) calculate drift relative to planned track;
  - (d) calculate the relative bearing which will indicate the aircraft is abeam a station;
  - (e) calculate the relative bearing which will indicate that a desired track to or from an NDB has been intercepted, given the intercept heading;
  - (f) calculate the heading to steer to intercept desired inbound track before reaching the NDB.
- 5.1.4 For lateral guidance provided by VOR course deviation indicator (CDI), describe the following:
  - (a) the cockpit indications of scalloping;
  - (b) the indications of loss of signal integrity;
  - (c) the indications of station passage.
- 5.1.5 Given VOR lateral course deviation indications, determine the position of the aircraft with reference to the VOR ground station.
- 5.1.6 VOR OBS settings required to provide command indications when flying on given tracks both to and from the VOR.
- 5.1.7 Determine aircraft position given cockpit instrument indications utilising a VOR.
- 5.1.8 Instrument indications when the aircraft is abeam the VOR on a given track.
- 5.1.9 DME including the following:
  - (a) the use of DME and its limitations;
  - (b) effect of aircraft altitude (slant range);
  - (c) effect when not tracking direct to and from the aid;
  - (d) DME arrival procedures.
- 5.1.10 ILS and LOC including the following:
  - (a) components of the ILS including marker beacons;
  - (b) operational considerations;
  - (c) errors including G/S fluctuations and course reversal indications.

**5.2 GNSS**

- 5.2.1 The GNSS system and its principles of operation, including the following:
- (a) GNSS system components;
  - (b) space segment;
  - (c) GNSS satellite signal;
  - (d) pseudo random code (C/A course acquisition code);
  - (e) control segment;
  - (f) user segment (the GNSS receiver);
  - (g) pseudo ranging;
  - (h) principle of position fixing/minimum satellites required for navigation functions;
  - (i) TSO/Performance limitations of various equipment types;
  - (j) RAIM;
  - (k) masking function;
  - (l) receiver displays of system integrity;
  - (m) operating modes – navigation with and without RAIM, DR;
  - (n) explain why GNSS use the WGS84 coordinate system;
  - (o) effect of PDOP/GDOP.
- 5.2.2 The following terms in relation to a navigational system and recall to what extent the GNSS system meets the associated requirements:
- (a) accuracy;
  - (b) integrity;
  - (c) means of providing GNSS integrity;
  - (d) RAIM, procedural, systems integration;
  - (e) availability;
  - (f) continuity of service.
- 5.2.3 Degradation of GNSS accuracy by the following GNSS errors:
- (a) ephemeris;
  - (b) clock;
  - (c) receiver;
  - (d) atmospheric/ionospheric;
  - (e) multipath;
  - (f) selective availability (SA);
  - (g) typical total error associated with c/a code;
  - (h) interference.
- 5.2.4 Requirements for use of GNSS in the following IFR operations:
- (a) en route;
  - (b) RNP instrument approach operations;
  - (c) alternates;
  - (d) RNP operations.
- 5.2.5 Pilots actions and implications for the following GNSS warnings and messages, including the following:
- (a) loss of RAIM;
  - (b) 2D navigation;
  - (c) in dead reckoning mode;
  - (d) database out-of-date;
  - (e) database missing/failure;
  - (f) GNSS fail;

- (g) barometric input fail;
  - (h) power/battery fail;
  - (i) parallel offset on.
- 5.2.6 Parameters applicable to tracking tolerances, automatic waypoint sequencing, CDI sensitivity and RAIM availability in each of the following segments:
- (a) en route;
  - (b) terminal;
  - (c) initial approach;
  - (d) intermediate approach;
  - (e) final approach;
  - (f) missed approach.
- 5.2.7 Indications requiring a missed approach to be initiated.
- 5.2.8 The effect of availability or otherwise of baro-aiding on RAIM availability and prediction.
- 5.2.9 Describe the effect of satellite unserviceability on the reliability of each type of prediction.

### **5.3 3D instrument approach operations**

- 5.3.1 Pilot responsibilities when conducting a 3D instrument approach operation utilising vertical guidance (advisory) provided by the aircraft navigation system on a 2D instrument approach procedure.
- 5.3.2 The different kinds of 3D instrument approach procedures.
- 5.3.3 The components required for a GNSS landing system (GLS) instrument approach procedure.
- 5.3.4 The principles of operation of a GBAS or local area augmentation system.
- 5.3.5 The validity of GLS guidance information beyond the distance of the GBAS station defined as D-Max.

## **6. Performance based navigation (PBN)**

### **6.1 Basic principles**

- 6.1.1 The basic principles of PBN, including requirements for RNAV and RNP capability.
- 6.1.2 The core components that make up the PBN airspace concept, including the following:
- (a) communications;
  - (b) navigation;
  - (c) surveillance (extended squitter ADS-B);
  - (d) air traffic management.
- 6.1.3 The navigation system performance requirements for PBN in respect to the following:
- (a) accuracy;
  - (b) integrity;
  - (c) continuity;
  - (d) functionality;
  - (e) installation requirements.
- 6.1.4 The function of performance monitoring and alerting in a navigation system approved for PBN operations.

### **6.2 RNP specifications**

- 6.2.1 RNP specifications and system requirements and their application for the following:
- (a) RNP 2 (en route);
  - (b) RNP 1 (terminal);
  - (c) RNP APCH – LNAV and LNAV/Baro VNAV;

- (d) RNP APCH – LP and LPV (SBAS).
- 6.2.2 The meaning of the specified RNP value, for example, RNP 1, in terms of the navigational accuracy.
- 6.2.3 The following RNP navigation system errors:
  - (a) FTE (flight technical error);
  - (b) PDE (path definition error);
  - (c) TSE (total system error);
  - (d) NSE or PEE (navigation system error/position estimation error).
- 6.2.4 The meaning of the following RNP leg types:
  - (a) TF (track to a fix);
  - (b) RF (constant radius to a fix);
  - (c) IF (initial fix);
  - (d) HF (hold to fix);
  - (e) HM (hold for clearance);
  - (f) HA (hold to altitude);
  - (g) DF (direct to a fix);
  - (h) FA (fix to an altitude);
  - (i) CF (course to a fix).
- 6.2.5 The meaning of the following leg transitions and their use in RNP operations:
  - (a) fly-by;
  - (b) fly-over;
  - (c) fixed radius (airspace design limitations).
- 6.2.6 The basic requirements for an RNP navigation authorisation and use of the following:
  - (a) communications;
  - (b) navigation;
  - (c) surveillance;
  - (d) airworthiness;
  - (e) continued airworthiness;
  - (f) flight operations.
- 6.2.7 The GNSS receiver requirements to conduct a RNP APCH operation.
- 6.2.8 The requirements to conduct an RNP instrument approach operation to a published Barometric Vertical Navigation (Baro/VNAV) minimum altitude.
- 6.2.9 The requirements to conduct a RNP instrument approach operation to a published Localiser Precision (LP) or LPV minimum altitude.
- 6.2.10 The conditions and actions that allow the GNSS receiver to function in the appropriate mode for the successful conduct of a RNP approach.
- 6.2.11 The difference between augmented and non-augmented approaches.
- 6.2.12 Interpret IAP charts and extract the correct minima for a given approach and any relevant operational restrictions.
- 6.2.13 The requirement for using a valid and accurate local QNH when conducting RNP approaches.
- 6.2.14 Differentiate between the following RNP approaches that provide 3D vertical guidance:
  - (a) RNP APCH – LNAV/VNAV (Baro VNAV);
  - (b) RNP APCH – LPV (SBAS required).
- 6.2.15 The basic principles of operation of a space-based augmentation system (SBAS) and the kind of minimum published altitudes that can be used when a SBAS is available.
- 6.2.16 Explain SBAS and how it affects RNP approaches.

- 6.2.17 Interpret APV Baro-VNAV instrument approach charts, including LNAV/VNAV minima, temperature limitations and vertical flight path angle.
- 6.2.18 Describe the difference between vertical guidance presented as linear deviation and angular deviation and the relevant operational considerations.
- 6.2.19 Demonstrate an understanding of the principles of Baro-VNAV vertical guidance, including path angle (VPA) construction and the effect of temperature variation from ISA on VPA.

## **7. Reduced Vertical Separation Minima (RVSM) operations**

- 7.1.1 Range of flight levels in which RVSM requirements apply within Australian airspace.
- 7.1.2 Operational requirements to conduct operations in designated RVSM airspace.
- 7.1.3 Requirements to ensure accuracy of aircraft altimeters are within prescribed tolerances to conduct operations in RVSM airspace.
- 7.1.4 Vertical height tolerance applicable when levelling off at assigned flight level in RVSM airspace.
- 7.1.5 Procedures and standard communication phraseology used for operations in RVSM airspace, including procedure following failure of 1 or all primary altimetry systems.

## **8. Human factors**

- 8.1.1 Physiological factors effecting human performance when conducting flight without visual reference, including the following:
  - (a) the part played by the vestibular systems, namely the semicircular canals and otoliths, in helping the pilot maintain orientation;
  - (b) the circumstances aggravate vestibular disorientation, and how to overcome this problem.
- 8.1.2 The circumstances that may aggravate vestibular disorientation such as somatogravic illusions and somatogyral illusions.
- 8.1.3 State conditions and causes under which visual illusions, such as 'false horizons', visual-cue illusions, relative motion illusions, 'flicker' effect, 'black hole' illusion, and autokinesis may occur.
- 8.1.4 GNSS operating procedures which provide safeguards against navigational errors and loss of situational awareness because of the following:
  - (a) mode errors;
  - (b) data entry errors;
  - (c) data validation and checking, including independent cross-checking procedures;
  - (d) automation induced complacency;
  - (e) non-standardisation of the GNSS receiver units;
  - (f) human information processing and situational awareness.
- 8.1.5 When conducting an instrument approach operation describe the benefits of utilising a CDFA technique from a human performance limitations perspective.